

ZONING ORDINANCE DIVISION 708 DISTRICT STANDARDS AND PERMITTED USES

708.22 LRO, Low Rise Office

A. Purpose and Intent.

The LRO district is intended to provide suitable areas for small scale professional offices and other non-retail oriented commercial uses such as offices and day care centers. This district provides a step down from more intense uses and is ideally located between residential zonings and more intense uses.

B. Permitted Uses.

- 1. Banks and financial institutions, including those with drive-in services and automatic tellers.
- 2. Cultural facilities.
- 3. Day care centers and nursery schools, provided:
 - a) Such use must obtain certification from the Georgia Department of Human Resources
 - b) Any outdoor play area shall be enclosed by a fence not less than 4 feet in height and located in the rear yard area of the principal building with a self-closing, self-latching gate.
- 4. Health service clinics.
- 5. Offices, professional and general office. Maximum gross floor area of 15,000 square feet.
- 6. Personal care facilities, provided:
 - a) Such use must obtain all necessary local and state licenses.
 - b) The maximum number of beds permitted shall not exceed one per 200 gross square feet.
- 7. Other uses which are substantially similar in character and impact to those uses enumerated above. Such uses must clearly meet the purpose and intent of this zoning district.
- 8. Accessory uses and structures incidental to any permitted use.

C. <u>Temporary/Conditional Uses Allowed by the Director</u>.

Not applicable in this district.

D. Special Uses Permitted by Board of Zoning Appeals.

Group homes (see standards set forth in Section 712.02).

E. Special Uses Permitted by City Council.

Not applicable in this district.

F. Accessory Structures.

- 1. All such structures shall be located upon the same lot and to the side or rear of the principal use at least 10 feet from side or rear lot lines. In cases of corner lots, the accessory structure may not be closer to any right-of-way than the principal building.
- 2. Any accessory building in excess of 1,000 square feet of gross space must meet the setback standards for a principal use and shall be architecturally compatible with the principal structure.
- 3. When an accessory building is attached to the principal building in any manner, it shall be deemed part of the principal structure and subject to all bulk and area requirements of same.
- 4. No accessory building shall be constructed upon a lot before the principal building, nor shall it contain a greater floor area than the principal structure.
- 5. No accessory structure may exceed the more restrictive of either 15 feet or the height of the principal building.
- 6. Swimming pools must be enclosed by a fence not less than 4 feet in height with a self-closing, self-latching gate and must comply with all applicable safety and health ordinances.



ZONING ORDINANCE DIVISION 708 DISTRICT STANDARDS AND PERMITTED USES

7. Heating and air conditioning units may encroach 5 feet into the required rear or side setback.

G. *Use Limitations*.

- 1. No outside storage is permitted.
- 2. Commercial vehicles parked on-site may be no larger than a step van.
- 3. No laboratories or clinics are permitted.
- 4. Lighting shall be established so that no direct light shall cast over any property line nor adversely affect neighboring properties.
- 5. Building design and materials may be of the developer's choosing; however, structures which utilize metal siding shall be constructed with brick, stone, rock or wood covering any facade of the building facing a roadway.

H. Bulk and Area Regulations.

Butte and Thea Regulations.	
Minimum Lot Size:	15,000 sq. ft.
Minimum Lot Width:	60 ft.
Maximum Building Height:	35 ft.
Maximum Floor Area Ratio	0.50
Maximum Impervious Surfa	ice: 75%
Minimum landscaped area:	15%
Front Setback (arterial):	40 ft.
Front Setback (collector):	35 ft.
Front Setback (local):	30 ft.
Side Setback (major):	25 ft.
Side Setback (minor):	15 ft.
Rear Setback:	30 ft.

I. <u>Landscape and Buffer Requirements.</u>

When a LRO district directly abuts a R-1. R-2, R-3, R-4, PRD-SF, RA-4, RA-6, or RA-8 district, a 30 ft buffer shall be established (see standards set forth in Section 710.05).

(Ord. No. 6149, 8/9/2000, Sec. 2)